

# FS-1100 SPECIFICATIONS

## PRINTER SPECIFICATIONS

### BASIC SPECIFICATIONS:

Configuration:	Small Workgroup Black & White Printer with 250 Sheet Drawer, Single Sheet Multi-Purpose Tray and Optional Network Card
Resolution:	Fine 1200 mode (1,200 x 1,200 dpi), Fast 1200 mode (1,800 x 600 dpi), 600 x 600 dpi, 300 x 300 dpi
Printer Memory:	Standard 32MB, upgradable to 544MB via 100 pin DDR DIMMs; Standard CF Card Slot (Type 1)
Electrical Requirements:	120V, 60Hz, 7.5A
Dimensions:	14.8"W x 15.5"D x 9.8"H
Weight:	22.1 lbs
Max Duty Cycle:	20,000 Pages Per Month

### CONTROLLER SPECIFICATIONS:

Controller:	PowerPC405F5/360MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), Diablo 630, IBM ProPrinter X24E, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL6/KPDL3, 1 Bitmap Font
Operating System Support:	Windows® 2000/XP/Vista; Mac OS 10.x; Linux
Connectivity / Interface:	Hi-Speed USB 2.0
KUIO LV Enhancement Slot:	Optional Network Interface (IB-23)
Network Support:	Please refer to IB-23 Section
Drivers:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers, Generic Driver for Windows Legacy
Utilities:	KM-NET Viewer, IC-Link, Status Monitor, PRESCRIBE Utilities

### PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Drawer, Single Sheet MPT
Drawer Paper Size:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio
MPT Paper Size:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio Custom (2.8" x 5.8" - 8.5" x 14.0")
Std/Max Paper Capacity:	251 Sheets/501 Sheets
Paper Weight:	16 - 32 lb Bond via Paper Drawer, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

### OUTPUT SPEEDS:

Warm-Up Time:	Less than 15 Seconds (From Sleep Mode)
First Print Out:	Less than 6 Seconds (EcoFuser Off)
Pages Per Minute:	30 Letter, 24 Legal

## PAPER HANDLING OPTIONS & ACCESSORIES:

### PAPER DRAWER: PF-100

Paper Capacity:	250 Sheets
Maximum Drawers:	1
Paper Weight:	16 - 32 lb Bond
Paper Sizes:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio
Dimensions / Weight:	14.7"W x 15.4"D x 3.9"H / 7.7lbs or less

### NETWORK INTERFACE CARD: IB-23

Interface:	KUIO LV
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Windows® Support:	Windows® 2000/XP/2003/Vista
Novell® Support:	Novell Netware® 5.x/6.x
Mac OS Support:	OS 9.x/10.x
UNIX OS Support:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Network Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI, NetBIOS over TCP/IP
Security Protocols:	IP Filtering, SSL/TLS (HTTPS), SNMP V2c/V3, IPv6, IEEE802.1x (EAP TLS/PEAP)
IPv6 Protocols:	HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMPv6
IPv4 Protocols:	HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMP, SMTP, POP3, SNMP, DNS, WINS, NetBIOS over TCP/IP, SNMP v1/v2c/v3, ThinPrint Compatible, Apple Bonjour Compatible
Utility:	KMnet Admin

### ADDITIONAL MEMORY:

Available Memory:	64MB, 128MB, 256MB and 512MB DDR DIMMS
-------------------	--

### CONSUMABLES:

Toner TK-142:	4,000 pages @ 5% Coverage
	Ships with 2,000 pages @ 5% Coverage, ISO 19752 Certified

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

Kyocera's ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today. Visit our TCO Tracker at [www.kyoceramita.com](http://www.kyoceramita.com) and start saving.



Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com).  
All trademarks and trade names are the property of their respective owners.  
Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008,  
Fairfield, NJ 07004-0008, USA  
©2008 Kyocera Mita America, Inc.  
IC#85D400126



[www.kyoceramita.com](http://www.kyoceramita.com)