

Copy 🌑 Scan

Print

Fax Dublish

Space to think Bigger

- Up to 32 pages per minute in A4, up to 16 pages per minute in A3
- 64 MB memory standard, upgradeable to 576 MB
- PDF direct printing from USB Flash Memory devices
- Eco-friendly, ozone-free technology
- Long-life components and easy maintenance
- Duplex unit and network connectivity as standard



Benefit from a rare combination of talents: high quality A3 output yet small footprint and a remarkably low noise level.



For workgroups that require a wide variety of output up to A3, at speed. This flexible new generation printer, with up to 1,000 sheets paper capacity, can accommodate increases in memory, especially helpful for CAD and DTP envir-onments. Low noise, compact design and cost-effective ECOSYS technology give you more space to think about big ideas.



Kyocera shape controlled toner makes the most of every one of the 1,200 dots per inch

FS-6950DN

🔇 КУОСЕRА

FS-6950DN A3 Monochrome Workgroup Printer

General

Technology:

Kyocera ECOSYS, Lase

Engine speed:

Up to 32/16 pages per minute A4/A3 simplex Up to 23/10 pages per minute A4/A3 duplex

Resolution

Fine1200, Fast1200, 600x600, 300x300

Time to first page:

9 seconds or less Warm-up time:

15 seconds or less from power on

Duty cycle:

Max. 150,000 pages per month, max. average 20,000 pages per month

Power source:

AC 220 ~ 240 V. 50/60 Hz

Power consumption

Printing: 555 W. Stand-by: 10 W.

Power-Saving (ECOpower): 4.9 W Noise (ISO 7779):

Printing: 50 dB(A), Stand-by: 40 dB(A),

Power-Saving (ECOpower): Immeasurably low

Dimensions (W x D x H):

Main unit: 469 x 395 x 285 mm

Weight: Main unit: Approx. 19.5 kg Certifications:

TÜV/GS, CE, PTS

This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling

All paper capacities quoted are based on a paper thick-ness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity:

250-sheet universal paper cassette,

60-120 g/m2, A3, B4, A4-R, A4, A5, B5, Letter, Letter-R, Legal, Ledger, Custom (139.7 x 148 mm to 297 x 432 mm) 100-sheet multi-purpose tray, 60-220 g/m2, A3, B4, A4R, A4, A5, A6R, B5, Letter, Letter, Letter, Legal, Ledger, Custom (70 x 148 mm to 297 x 450 mm)

Max. input capacity with 4 optional paper feeders PF-430: 1,350 sheets



Ecosys

ECOSYS devices are designed to minimise both direct costs and indirect costs, such as maintenance, administration and consumables. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow-enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's longlife components cost you and the environment less.

In an effort to reduce future landfill pollution Kyocera has removed 6 hazardous materials from our latest products. Kyocera has implemented a totally lead free manufacturing process using lead free solder and components.



Disclaimer

Duplex as standard supports A3-A5-R, 60-120 g/m2

Output capacity:

250 sheets face-down with paper full sensor and optional 250 sheets face-up with PT-430

Controller

Processor: PowerPC 750 / 400 MHz

Memory:

Standard 64 MB + ECOmemory, max. 576 MB

Emulations:

PCL6/PCL5e incl. PJL, KPDL 3 (PostScript 3 compatible). PDF direct print, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, KCGL (HP 7550A)

Controller language:

PRESCRIBE IIe

Fonts:

80 outline fonts accessible in all emulations,

1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417,

Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format

Print features:

Duplex, Accounting, PDF direct printing, eMPS, low noise, no Ozone, USB-Host

Interfaces

Standard interface:

High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), Fast Ethernet 10Base-T/100Base-TX, USB Host Interface dedicated for USB Flash Memory device, KUIO-LV option interface slot

Multiple interface connection (MIC):

Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

Options Paper handling

PF-430 Paper feeder (max. 4 units): 250 sheets, 60-120 g/m2, A3, B4, A4-R, A4, A5, B5, Letter, Letter-R, Legal, Ledger, Custom (139.7 x 148 mm to 297 x 432 mm)

PT-430 Paper tray: 250 sheets face-up output tray

Memory

Printer memory: 1 DDR SDRAM DIMM slot (64, 128, 256 or 512 MB)

System platform:

T PT-430

The FS-6950DN offers USB, parallel and network connectivity as standard and delivers problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network; from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Client/KM-NET Viewer:

The settings of all printers on the network can be checked visually and amended from any Windows® PC. KM-NET for Client enables easy setup and monitoring of the printer status via parallel, USB or network connection. KM-NET Viewer is an advanced printer management software tool using the standardized protocol SNMP.

Storage memory: 1 slot for either CompactFlash® memory card type 1 (up to 2 GB) for forms, fonts, logos, macro storage or MicrodriveTM (up to 4 GB) for forms, fonts, logos, macro storage as well as document manage-ment with eMPS functions such as quick copy, proof and hold, private print and job storage.

1 USB Host Interface (USB 1.1) for USB Flash Memory device supports PDF direct printing

Optional interface

IB-21E Network card: 10Base-T/100Base-TX IB-11 Serial interface: RS-232C serial interface

(max, 115.2 kbps)

IC159-WLAN: KUIO PORT 802.11b Wireless Lan Card

Consumables

TK-440 Toner-kit: Microfine toner for 15,000 pages with 5% coverage (ISO/IEC 19752)

Capacity of starter toner is 7,500 pages with 5% coverage (ISO/IEC 19752)

MK-440 Maintenance Kit: Due for installation at each 300,000 images.

Warranty

2-year onsite warranty as standard.

Kyocera guarantees the drum and developer for 2 years or 300,000 images (whichever occurs sooner), provided each printer is used, cleaned and maintained in accord ance with the service instructions.

Extended Warranty Options

ECO-FS-3003: Optional Upgrade to 3rd year onsite

ECO-FS-3004: Optional Upgrade to 4th year onsite warranty

Model configurations

FS-6950DN ES-6950DTN (ES-6950DN + PE-430)

3x PF-430

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to print. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

Australia Sales Enquiries 1300 364 429

Australia Web Address www.kyoceramita.com.au

New Zealand Web Address www.kyoceramita.co.nz

Sydney Head Office

6-10 Talavera Road North Ryde NSW 2113 Phone: (02) 9888 9999 Fax: (02) 9888 9588

Melbourne Office

Brisbane Office

West End QLD 4101

Fax: (07) 3844 8569

104 Walters Drive

Perth Office

Phone: (07) 3844 6686

Osborne Park WA 6017

Phone: (08) 9201 9155

Fax: (08) 9201 9511

Adelaide Office

53 Rundle Street,

Kent Town SA 5067

Fax: (08) 7421 2001

Canberra Office

Epicorp Centre

Acton ACT 2601

Phone: (08) 7421 2000

401 Clunies Ross Street

Phone: (02) 6229 1729

New Zealand Office

Fax: (02) 6229 1701

1-3 Parkhead Place

Albany New Zealand

Fax: (649) 415 4597

Phone: (649) 415 4517

ABN 77 003 852 444

Kyocera is the

Official Supporter of

Business Clean Up Day

A SMART

ENVIRONMENTAL

CHOICE

Protection of the environment

is integral to Kyocera's

day-to-day operations. Research

over the last few decades has

been focused, not only

developing the most advanced

document management devices,

but also doing so in harmony

with the environment.

o, an

Unit 2, 993 North Road Murrumbeena VIC 3163 Phone: (03) 9579 1555 Fax: (03) 9579 1544

Cnr Forbes St & Riverside Drive