



Document Solutions

> PRINT

ECOSYS P5021cdn
ECOSYS P5021cdw
ECOSYS P5026cdn
ECOSYS P5026cdw

COLOR PRINTER
FOR A4 FORMAT

BRIGHT COLOR BUSINESS PRINTING



KYOCERA MyPanel



Mobile Print



- Quick A4 print up to 26/26 ppm (Mono/Color) (ECOSYS P5026cdn / P5026cdw).
- Convenient built-in wireless LAN interface (ECOSYS P5021cdw / P5026cdw).
- Equipped with robust features like standard duplex unit for double-sided printing and direct printing from USB.
- Support Air Print and Mopria certified.
- Standard 512MB RAM to perform heavy duty tasks without additional memory required.
- High printing quality with 1,200 x 1,200 dpi print resolution.



		Main Specifications			
Model		ECOSYS P5021cdn	ECOSYS P5021cdw	ECOSYS P5026cdn	ECOSYS P5026cdw
Type		Desktop			
Writing Method		Semiconductor Laser			
Print Speed (A4) (Mono/Color)		21/21 ppm		26/26 ppm	
First Print Out Time (Mono/Color)		11/12.5 seconds		9.5/10.5 seconds	
Warm Up Time		32 seconds		29 seconds	
Resolution		600 x 600 dpi, 1,200 x 1,200 dpi			
Duplex		Auto			
Control Panel		2 lines LCD Panel			
Power Consumption (Standard configuration)	Print Mode	345W		375W	
	Stand-by Mode	33W			
	Sleep Mode	0.9W			
Noise (ISO7779/ ISO9296)	Print Mode	48dB(A); Quiet Mode: 44dB(A)		49dB(A); Quiet Mode: 44dB(A)	
	Stand-by Mode	30dB(A)			
Dimension (W x D x H) (Main Unit)		410mm x 410mm x 329mm			
Weight (Main Unit)		Approx. 21 kg			
		Controller			
CPU		800MHz			
Memory		Standard 512MB (Max. 512MB)			
Interface		USB 2.0 High Speed x1; Ethernet 10BASE-T/100BASE-TX/1000BASE-T; USB Host x1; 802.11 b/g/n/Wireless LAN/WiFi Direct (ECOSYS P5021cdw/ECOSYS P5026cdw only)			
PDL		PRESCRIBE, PCL6 (PCL5c, PCL-XL), KPDL3 (Postscript 3 compatible), PDF Direct Print Ver. 1.7			
Network Printing		TCP/IP, NetBEUI, FTP, Port 9100, LPR, IPP, WSD Print, Apple Bonjour, IPsec, SNMPv3, IEEE802.1x, IPP over SSL/TLS, HTTP over SSL/TLS, FTP over SSL/TLS, SMTP over SSL/TLS, POP3 over SSL/TLS, Enhanced WSD over SSL/TLS			
Operating System Supported		Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows XP, Windows Vista, Windows 7, Windows 8, Windows 8.1; Apple Macintosh OS X 10.5 or later, Linux			
USB Memory Printing		Standard			
USB Memory Printing Format		TIFF, JPEG, PDF, XPS			
Mobile Printing		AirPrint, Mopria, KYOCERA Mobile Print			
		Paper Handling			
Paper Capacity	Standard	250 sheets x1 (Cassette) + 50 sheets (MPT)			
	Maximum	550 sheets (Main Unit + PF-5110 x1 + MPT)			
Paper Size	Cassette	Min. A6R – Max. A4 (Legal)			
	MPT	Min. A6R – Max. A4 (Legal)			
Paper Weight	Cassette	60 – 163 g/m ²			
	MPT	60 – 220 g/m ²			
Duplex Printing		Paper size: A5R – A4/Legal; Paper weight: 60 – 120 g/m ²			
Output Capacity		Max. 150 sheets face-down			
		Consumables & Options			
Toner Kit (Page Yield in accordance with ISO/IEC 19798)		TK-5234K : Black (2,600 pages) TK-5234C/M/Y : Cyan/Magenta/Yellow (2,200 pages) TK-5224K : Black (1,200 pages) TK-5224C/M/Y : Cyan/Magenta/Yellow (1,200 pages)	TK-5244K : Black (4,000 pages) TK-5244C : Cyan (3,000 pages) TK-5244M : Magenta (3,000 pages) TK-5244Y : Yellow (3,000 pages)		
Capacity of Start Up Toner		Black 1,200 pages, Cyan/Magenta/Yellow 1,200 pages			
Paper Feeder		PF-5110 : 250 sheets (Max. x1)			
Card Authentication		Card Authentication Kit(B)			



บริษัท เคียวเซรา ด็อกคิวเม้นท์ โซลูชันส์ (ประเทศไทย) จำกัด

โทร. 0-2586-0333 โทรสาร 0-2586-0278

www.kyoceradocumentsolutions.co.th

KYOCERA Business Partner

*KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.