



Document Solutions

> PRINT > COPY > SCAN > FAX

ECOSYS M2040dn (3-in-1)

ECOSYS M2540dn (4-in-1)

ECOSYS M2640idw (4-in-1)

MONOCHROME MULTIFUNCTION
PRODUCT FOR A4 FORMAT

GENUINE MFP, WITH HIGH RELIABILITY AND PRODUCTIVITY



KYOCERA MyPanel



Mobile Print



- Speedy A4 copy/print up to 40 ppm (Mono).
- Standard 512MB RAM to perform heavy duty tasks without additional memory required.
- Support Air Print and Mopria certified.
- Convenient built-in wireless LAN interface*.
- User friendly 4.3 inch color touch screen panel*.
- Fast scanning up to 40/23 ipm Mono/Color.
- Standard high productive 50-sheet capacity one-path duplex scanning document processor.
- Low temperature fuser system for less power consumption.
- High printing quality with Fine 1,200 print resolution.

*For ECOSYS M2640idw



		Main Specifications	
Model		ECOSYS M2040dn	ECOSYS M2540dn
Main Function		Copy, Print, Scan, Fax (ECOSYS M2540dn/M2640idw only)	
Writing Method		Semiconductor Laser	
CPU		Cortex-A9 800 Mhz	
Print Speed (A4) (Mono)		40 ppm	
Scanning Speed (A4) 300dpi (Mono/Color)	Simplex	40/23 ipm	
	Duplex	32/16 ipm	
Memory		Standard 512MB (Max. 1,536MB)	
Warm Up Time		17 seconds	20 seconds
Paper Capacity	Standard	250 sheets (Cassette) + 100 sheets (MPT)	
	Maximum	850 sheets (Main Unit + 250 sheets PF-1100 x2 + MPT)	
Paper Size	Cassette	Min. A6R - Max. A4 (Legal)	
	Option	Min. A6R - Max. A4 (Legal)	
	MPT	Min. 70mm x 148mm - Max. A4 (Legal)	
Paper Weight	Cassette	60 - 163 g/m ²	
	Option	60 - 163 g/m ²	
	MPT	60 - 220 g/m ²	
Duplex Printing		Paper size: A5R - A4/Legal; Paper weight: 60 - 163 g/m ²	
Output Capacity		Max. 150 sheets face-down	
Control Panel		5 lines LCD (128 x 64 dot)	4.3 inch Color Touch LCD Panel
Document Processor		Standard (Max. 50 sheets one-path duplex scanning Type)	
Dimension (W x D x H) (Main Unit)		475mm x 412mm x 437mm	
Weight (Main Unit)		Approx. 19.0kg	
Power Consumption (Standard configuration)	Copy/Print Mode	661W	
	Stand-by Mode	21W	
	Energy Saver	1W	
Noise (ISO7779/ ISO9296)	Copy/Print Mode	52dB(A); Silent mode: 48dB(A)	
	Stand-by Mode	29dB(A)	
Copy Functions (Standard)			
Copy Size		Min. A6R - Max. A4 (Legal)	
Resolution		600 x 600 dpi	
First Copy Time (Mono/Color)		6.4 seconds or less	
Zoom Ratio	Manual	25% - 400% (1% per Step)	
	Pre-defined	7R5E	
Multiple Copy		1 - 999	
Print Functions (Standard)			
Resolution		600 x 600 dpi, Fast 1200, Fine 1200	
PDL/Emulations		PCL6 (PCL5e, PCL-XL), KPDL3 (Postscript 3 compatible), PRESCRIBE, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF Direct Print Ver. 1.7	
First Print Out Time		6.4 seconds or less	
Supported Protocol		NetBEUI, FTP, Port 9100, LPR, IPP, IPP over SSL, WSD Print, Apple Bonjour, IPsec, SNMPv3, IEEE802.1x, IPP over SSL/TLS, HTTP over SSL/TLS, FTP over SSL/TLS, SMTP over SSL/TLS, POP3 over SSL/TLS, Enhanced WSD over SSL/TLS	
Operating System Supported		Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2; Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows 10; Apple Macintosh OS X 10.5 or later; Linux	
Interface		USB 2.0 High Speedx1; Ethernet 10BASE-T/100BASE-TX/1,000BASE-T; USB Host Interface (USB Host)x1; 802.11 b/g/n/Wireless LAN/WiFi Direct (ECOSYS M2640idw only)	
USB Memory Printing Format		TIFF, JPEG, PDF, XPS, Open XPS	
Mobile Printing		AirPrint, Mopria, KYOCERA mobile print	
Scan Functions (Standard)			
Color Selection		Full Color; Grayscale; Black & White	
Resolution		600dpi, 400dpi, 300dpi, 200dpi, 200x400dpi, 200x100dpi	
File Format		TIFF, JPEG, XPS, PDF (MMR/JPG/High-compression PDF), PDF/A, Encrypted PDF	
Image Type Mode		Text, Photo, Text + Photo, Light text + Fine line, OCR (mono)	
Transmission Type		Scan to SMB; Scan to E-mail; Scan to FTP or FTP over SSL; Scan to DFS; Scan to USB; TWAIN Scan; WSD Scan, WIA	
Address Storage		200 addresses (Common address list), 50 groups (Group address list)	
Fax Functions (ECOSYS M2540dn/M2640idw only)			
Original Size		Min. A6 - Max. A4 (Legal)	
Coding Method		MMR, MR, MH, JBIG	
Transmission Speed		33.6 kbps	
Memory		3.5MB	
One Touch Dial	-	22 numbers	100 numbers
Network FAX		Yes	
Consumables & Options			
Toner Kit (Page Yield in accordance with ISO/ IEC 19752)		TK-1174 (7,200 pages)	
Capacity of Start up Toner		3,600 pages	
Maintenance Kit		MK-1154 (100,000 pages)	
Paper Feeder		PF-1100: 250 sheets (Max. x2)	
Card Authentication		Card Authentication Kit(B)	



Document Solutions

บริษัท เคียวเซระ ด็อกคิวเม้นท์ โซลูชันส์ (ประเทศไทย) จำกัด
โทร. 0-2586-0333 โทรสาร 0-2586-0278
www.kyoceradocumentsolutions.co.th

*KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



KYOCERA Business Partner